


# Maintainer

## 8000 Series Crane

### Features

- 8,600 LB. maximum lift capacity
- 7,500 lb. lift capacity @ 6' from center line of rotation
- 24 feet hydraulic reach
- 615 degrees of rotation
- Hexagonal boom design
- Tall tower crane pedestal design (short tower optional)
- Closed center/load sensing hydraulics (open center optional)
- Quick change load hook for single part line use
- Compact Anti-two block design

Meets OSHA  
1910.180  
requirements and  
ANSI B30.5 safety  
standards




8  
0  
0  
0  
C  
R  
A  
N  
E



## 8000 SERIES CRANE CAPACITY CHART **52600 FT\*LB** CRANE RATING

MAX SINGLE LINE CAPACITY IS 4300 LBS (1950 KG)  
FOR GREATER LOADS USE 2 PART LINE



1701 S 2ND AVE SHELDON, IA 51201  
800-831-8588  
WWW.MAINTAINER.COM

### Winch:

- **38:1 Ratio worm gear winch with brake (standard), 30 feet/min line speed, single**
- **40.5:1 Ratio planetary winch with brake (optional) 60 feet/min line speed, single**
- **Equipped with 120' of 3/8" cable**
- **ANSI winch drum**
- **Hydraulic high torque winch motor**

### Rotation:

- **Turntable slewing ring bearing**
- **Self-locking modular worm drive with spur gear output, 190.4:1 ratio**
- **Hydraulic rotation powered by a high torque motor**
- **615 Degrees of hydraulic rotation**

### Crane Physical Specifications

- **60.5" Overall crane height**
- **Wt. 2050 lbs. (930 KGS.)**
- **22" x 22" Mounting space required**
- **Mounting requires eight (8) 7/8-9 (GRD -8) bolts**
- **Hydraulic requirements 10-12 GPM@3000 PSI**

### Optional Equipment:

- **Wireless remote control, (plug & play)**
- **Planetary winch, (bolt on change out)**



Call for the dealer nearest you at 800.831.8588  
or on the web at [www.maintainer.com](http://www.maintainer.com)